



Europäisches Patentamt  
European Patent Office  
Office européen des brevets



(11) Publication number: **0 184 231 B1**

(12)

## EUROPEAN PATENT SPECIFICATION

(45) Date of publication of patent specification: 22.01.92 (51) Int. Cl.<sup>5</sup>: G01V 1/18, F16F 3/00

(21) Application number: 85201658.3

(22) Date of filing: 10.10.85

The file contains technical information submitted  
after the application was filed and not included in  
this specification

(54) Geophone spring.

(30) Priority: 30.11.84 US 676524

(43) Date of publication of application:  
11.06.86 Bulletin 86/24

(45) Publication of the grant of the patent:  
22.01.92 Bulletin 92/04

(84) Designated Contracting States:  
AT BE CH DE FR GB IT LI LU NL SE

(59) References cited:  
FR-A- 2 302 530  
FR-A- 2 454 020  
US-A- 2 947 529  
US-A- 4 285 054  
US-A- 4 504 932

(73) Proprietor: HALLIBURTON GEOPHYSICAL  
SERVICES, INC.  
6909 Southwest Freeway, P.O. Box 36306  
Houston Texas 77236(US)

(72) Inventor: Hagedoorn, Lourens Arend  
27, Scharemarkt  
NL-2311 PH Leiden(NL)  
Inventor: Vitringa, Frederick Anton  
14, Nobel Road  
Quathiaskicove, B.C. V0P 1N0(CA)

(74) Representative: Keyser, Johannes Maurits L.  
F. et al  
EXTERPATENT Willem Witsenplein 4  
NL-2596 BK The Hague(NL)

EP 0 184 231 B1

Note: Within nine months from the publication of the mention of the grant of the European patent, any person may give notice to the European Patent Office of opposition to the European patent granted. Notice of opposition shall be filed in a written reasoned statement. It shall not be deemed to have been filed until the opposition fee has been paid (Art. 99(1) European patent convention).

## Description

This invention relates to a geophone spring system for suspending a reference mass comprising first spring means for centering the mass both along and laterally to a main axis of the geophone, said first spring means consisting of an outer ring surrounding a middle ring and being connected thereto by legs. Geophones including such a spring system are disclosed e.g. in US-A-4 285 054.

Geophones are devices which sense motion by suspending an inertial reference mass structure from a rigid, fixed supporting structure. Typically, the mass is a coil form suspended by springs in a magnetic field, one spring being attached at each end of the coil form. The springs position the coil form within the magnetic field so that the coil form is centered laterally and along its axis within the magnetic field. The springs also form a suspension system having a predetermined resonant frequency.

In seismic operations, seismic waves are imparted into the earth's crust at or near the earth's surface, and portions of those seismic waves are reflected or refracted from the boundaries of subsurface layers. Geophones are arranged in arrays or groups on the earth's surface, and when the reflected or refracted waves encounter a geophone, the coil form, which is suspended between the two springs, tends to stand still while the geophone housing and its connected magnetic circuit moves with the earth's surface. The movement of the coil form through a magnetic field causes a voltage to be generated at the output of the geophone. The outputs of the arrays of geophones are recorded in a form which permits analysis. Skilled interpreters can discern from the analysis the shape of subsurface formations, and the likelihood of finding an accumulation of minerals, such as oil and gas.

In present day geophones, spider springs are used extensively. Such springs are usually made from discs of spring material and have an inner ring and an outer ring which are connected by a plurality of legs. The legs are formed by etching or stamping the spring material in accordance with a predetermined pattern. Generally three such legs are used, and the three-legged arrangement is generally considered the most advantageous.

The legs of geophone springs generally have a rectangular cross-section and are curved along their lengths between the junctures with the inner and outer rings of the spring. After etching, the spring is "preformed" according to known techniques. When preforming is complete, the inner ring is offset or displaced relative to the outer ring, such that when a mass is suspended between two such springs, the inner ring, legs, and outer ring of each spring lie in the same plane.

A geophone is intended to sense motion from a direction which is roughly parallel to the axis of movement of the coil form with respect to the geophone housing. Therefore, it is desirable to eliminate or minimize the effects of any lateral motion of the coil form in response to forces which are not parallel to the axis of movement of the suspended coil form within the geophone.

In seismic operations, an impulse which is not truly parallel with the geophone axis and which contains a frequency component at or very near to that of the spurious frequency causes the geophone to produce an undesired or false EMF in the coils. Because of its high Q, the movement will continue for some time after the force which caused it has subsided. This resonance is considered to be the main spurious frequency in a geophone and it is highly undesirable as it limits the geophone's upper clean bandwidth.

Inasmuch as the geometry and the mass of the coil form for a given model of geophone are constant within the manufacturing limits, the spurious resonance is also constant. The frequency of the spurious resonance can therefore be raised or lowered by changing the geometry of the suspension springs. This is mentioned in Fr-A-2.454.020. This characteristic has been used to raise the frequency of these false signals until they are beyond the desirable frequency spectrum of the geophone by increasing the lateral stiffness of the spring. With this approach, these false signals do not interfere with or corrupt signals of interest. A common method of increasing the lateral stiffness of the spring is to shorten the spring legs. Unfortunately, the signal distortion caused by spring nonlinearity is increased when the legs are relatively short, and spring life is reduced.

It has been recently discovered that for a spring having a natural frequency of 10 hertz or less, a ratio of about 50 to 1 of the spurious resonant frequency to the natural frequency of the geophone can be achieved by straightening the legs as much as possible (see applicant's EU-A-85201674.0). Such springs exhibit a clean bandwidth at frequencies higher than previously thought possible. However, the useful life of such springs is shorter than other springs which exhibit less lateral stiffness and more lateral elasticity, because the stiffness of the legs does not allow the coil form to hit its normal intended stops for violent lateral movements. Accordingly, the art has sought to extend the useful life of laterally stiff geophone springs.

The art has sought an effective, simple device to give lateral elasticity to the two types of laterally stiff geophone springs: those having a high natural frequency, and those having a high ratio of the spurious resonant frequency to the natural frequency.

cy. Such lateral elasticity has been deemed desirable in order to withstand rapid acceleration or deceleration as encountered in hard usage or destruction tests of a geophone.

In accordance with the present invention, a geophone spring is provided having both durability and high spurious frequency. This is realized in a geophone spring system which is characterized by second spring means for centering the reference mass laterally and for providing a damped compliance laterally to said axis to prevent the first spring means from being stressed beyond its elastic limit, and which damping is sufficiently heavy to prevent the second spring means from oscillating.

Thus a geophone spring system is provided which comprises two parts for different purposes for suspending a reference mass. The first part suspends the reference mass and also centers the reference mass laterally and along its axis. The second part also centers the reference mass laterally, but in addition provides a heavily damped compliance in a radial direction. This prevents the spring of the first part from being stretched beyond its elastic limits.

A preferred embodiment is characterized in that the second spring means comprise an inner ring connected to the middle ring by six arms of substantially equal length. In another embodiment, the lateral compliance device may, provided it can be heavily damped, be near the outer perimeter of the spring disc.

A geophone spring in accordance with the present invention, when compared with previously used springs, has the advantage of maintaining substantially linear performance even after having been subjected to the abnormally strong lateral forces experienced in rough handling or destruction tests. Furthermore, unexpected results of recent tests have shown that the invention when properly applied greatly reduces the amplitude of spurious resonance.

The invention will be clarified with reference to the accompanying drawings.

Figure 1 is a planar view of one embodiment of a geophone spring in accordance with the invention and

Figure 2 is a cross-sectional view of a known geophone in which two springs in accordance with the invention may be applied.

Referring to fig. 1, there is illustrated a geophone spring 1 in accordance with the present invention. The geophone spring is made from a thin, disc-shaped material such as beryllium copper.

The geophone spring 1 comprises an outer ring member 2, a middle ring member 3 and an inner ring member 4. The outer ring member 2 and the middle ring member 3 are connected by a

plurality of legs 5, which are formed by removing those portions of the disc designated 6. Preferably, this removal is effected by known etching techniques.

Still referring to fig. 1, the geophone spring 1 includes an inner spring which is formed between the middle ring member 3 and the inner ring member 4. The middle ring member 3 and the inner ring member 4 are connected by arms 7. The arms 7 are formed by removing those concentric portions of the disc designated 8, 9 and that removal can be done by etching or stamping. The inner spring can be stamped or etched in any geophone spring, and is shown incorporated into a delta-shaped geophone spring 1.

As noted above, the configuration and number of the etchings to form the inner spring may be varied as desired or required.

In a preferred embodiment, although the outer spring of the geophone spring 1 may be flat or preformed, the inner spring is not preformed, but remains flat. The six arms 7 are preferably substantially equal in length, and are as long as possible. The width of the arms 7 can be increased to give greater stiffness to the lateral compliance action of the inner spring, or a concentric set of arms can be added to decrease the lateral stiffness.

Referring to fig. 2, a geophone has two geophone springs 1, one on the top and one on the bottom of the coil form 10. When installed in a geophone, the outer spring of each spring 1 supports approximately one-half the weight of the coil form 10 and each spring 1 is substantially flat when the coil form 10 is in the rest position. As the outer spring of the spring 1 supports the coil form 10, it also centers the coil form 10 along the vertical axis of the geophone.

When the geophone spring 1 is installed on the bottom of the coil form, a pressure ring 11 pushes the middle ring member 3 against the flat surface of a pole piece shoulder 12. The frictional effect of the flat surface of the middle ring member 3 being held against the flat surface of the pole piece shoulder 12 dampens any lateral resonances that could be produced during normal operation.

When a second geophone spring 1 is installed on the top of the coil form, a contact ring 13 pushes the middle ring member 3 against the flat surface of a pole piece shoulder 12. The same frictional effect described above also operates with the second spring 1 on the top of the coil form.

During rough handling or destruction tests, the arms 7 will flex to allow the coil form 10 to hit its lateral stops. The coil form 10 has a gap 14 on either side. To the left of the gap 14a is a pole piece 15. To the right of the gap 14b is a geophone case 16. Both the inner spring and the outer spring of the spring 1 center the coil form 10

laterally between the pole piece 15 and the case 16. The pole piece 15 and the geophone case 16 are the lateral stops which stop the lateral motion of the coil form 10.

The legs 5 are too stiff by themselves to allow sufficient lateral movement and, therefore, they absorb the shock to their detriment if the lateral compliance device is not added. Since the arms 7 flex to allow the coil form 10 to hit both the pole piece 15 and the case 16, the legs 5 do not have to absorb the shocks. This extends the useful life of the legs 5, and thus of the spring 1.

The foregoing description of the invention has been directed in primary part to a particular preferred embodiment. It will be apparent, however, to those skilled in this art that many modifications and changes in this specific device may be made without departing from the scope of the invention. For example, the rings 6, 7 could be in the shapes of triangles, squares, or even irregular polygons. Alternatively, the inner spring could be in a plane above or below the existing spring.

#### Claims

1. A geophone spring system for suspending a reference mass (10) comprising first spring means (2, 3, 5) for centering the mass both along and laterally to a main axis of the geophone, said first spring means consisting of an outer ring (2) surrounding a middle ring (3) and being connected thereto by legs (5), characterized by second spring means (4, 7) for centering the reference mass laterally and for providing a damped compliance laterally to said axis to prevent the first spring means from being stressed beyond its elastic limit, and which damping is sufficiently heavy to prevent the second spring means from oscillating.
2. A geophone spring system according to claim 1, characterized in that the second spring means comprise an inner ring (4) connected to the middle ring (3) by six arms (7) of substantially equal length.

#### Revendications


1. Système de ressorts pour géophone pour la suspension d'une masse de référence (10), comprenant de premiers moyens élastiques (2, 3, 5) pour centrer la masse de référence le long d'un axe principal du géophone et latéralement par rapport à celui-ci, lesdits premiers moyens élastiques consistant en un anneau extérieur (2) qui entoure un anneau central (3) à qui il est relié par des branches (5), caractérisé par de deuxièmes moyens élasti-

ques (4, 7) pour un centrage latéral de la masse de référence et pour conférer une élasticité latérale atténuée par rapport audit axe, pour éviter que les premiers moyens élastiques soient sollicités au-delà de leur limite élastique, cette atténuation étant suffisamment forte pour éviter une oscillation des deuxièmes moyens élastiques.


2. Système de ressort pour géophone selon la revendication 1, caractérisé par le fait que les deuxièmes moyens élastiques comprennent un anneau intérieur (4), relié à l'anneau central (3) par six branches (7) de longueur sensiblement égale.

#### Patentansprüche

1. Federsystem für ein Geophon zur Aufhängung einer Referenzmasse (10) mit einer ersten Federanordnung (2, 3, 5) zur Zentrierung der Masse in axialer und lateraler Richtung bezüglich der Hauptachse des Geophon, diese Federanordnung bestehend aus einem äußeren Ring (2), der einen mittleren Ring (3) umschließt und durch Federbeine (5) mit diesem verbunden ist, gekennzeichnet durch eine zweite Federanordnung (4, 7), die zur lateralen Zentrierung der Referenzmasse dient und die eine gedämpfte Federung in bezüglich der Achse lateraler Richtung zur Verhütung einer Überbeanspruchung der ersten Federanordnung über die Grenze ihrer Elastizität hinaus bewirkt, wobei die Dämpfung groß genug ist, um ein Oszillieren der zweiten Federanordnung zu verhindern.
2. Federsystem für ein Geophon nach Anspruch 1, dadurch gekennzeichnet, daß die zweite Federanordnung einen inneren Ring (4) aufweist, der mit dem mittleren Ring (3) durch sechs Federarme (7) von im wesentlichen gleicher Länge verbunden ist.



**FIG. 1.**



**FIG. 2.**